



YSI Pro20

Portable dissolved oxygen & temperature meter

The **YSI Pro20** is a rugged, user-friendly instrument for measuring dissolved oxygen (DO), barometric pressure, and temperature. Galvanic and polarographic DO sensors are available for field use, while a BOD probe is available for lab use.

In addition to its impact-resistant, waterproof handheld display, the Pro20 has features that make field sampling faster and easier.



User-replaceable cables and sensors



One Touch Cal for DO calibrations within seconds



50 data set memory

Pro20 handheld specifications

Size (W x L x D)	8.3 cm x 21.6 cm x 5.7 cm (3.25 in x 8.5 in x 2.25 in)
Weight (with batteries)	475 grams (1.05 lbs)
Power	2 alkaline C-cell batteries providing 400 hours of battery life (without backlight)
Operating temperature	-5 to 55 °C
Storage temperature	-20 to 70 °C
Cable	1-, 4-, 10-, 30-, and 100-meter lengths with military-spec connectors
Warranty	3-year instrument; 2-year cable; 1-year sensor
Data memory	50 data sets
Languages	English, Spanish, Portuguese, French
Certifications	RoHS, CE, FCC, IP-67, 1-meter drop test, Assembled in USA

Pro20 sensor specifications (Instrument, sensor, and cable)

	Range	Resolution	Accuracy
Temperature (°C, °F, K)	-5 to 55 °C	0.1 °C	±0.3 °C
Dissolved Oxygen % Saturation (galvanic or polarographic)	0 to 500% air saturation	0.1% or 1% air saturation (selectable)	0 to 200%: ±2% of the reading or ±2% air saturation, whichever is greater; 200 to 500%: ±6% of the reading
Dissolved Oxygen mg/L (galvanic or polarographic)	0 to 50 mg/L	0.01 or 0.1 mg/L (selectable)	0 to 20 mg/L: ±2% of the reading or ±0.2mg/L, whichever is greater; 20 to 50 mg/L: ±6% of the reading
Barometer (mmHg, inHg, mbar, psi, kPa)	500 to 800 mm Hg	0.1 mm Hg	±3 mm Hg within ±15 °C range from calibration point



xylem

YSI Incorporated
1725 Brannum Lane
Yellow Springs, OH 45387

Tel +1 937.767.7241
Email info@ysi.com
ysi.com



xylem
Let's Solve Water